



Fire Fighting Solutions

Umfassender Brandschutz der Extraklasse



## **BAVARIA** Portable Gel Extinguisher

Internal cartridge operated

Type: **Magnum Water Glue**

### **Einsatz:**

BAVARIA Magnum Water Glue can be used both as an extinguisher for A-fires as well as in particularly for the lithium-ion batteries.

Water Glue is adhesive and heat absorbing gel, with extinguishing and also protective properties. The extinguisher is highly recommended for any companies, which are working with lithium-ion batteries.



**BAVARIA®**  
Fire Fighting Solutions

**BAVARIA Brandschutz Industrie GmbH & Co. KG**  
Regensburger Straße 16  
D-93449 Waldmünchen  
Telefon: +49(0)9972.94 01 0  
Telefax: +49(0)9972.94 01 17  
Thomas-Mann-Straße 61a  
D-90471 Nürnberg  
Telefon: +49(0)911.598 48 00  
Telefax: +49(0)911.598 48 01  
[info@bavaria-firefighting.de](mailto:info@bavaria-firefighting.de) · [www.bavaria-firefighting.de](http://www.bavaria-firefighting.de)

**BAVARIA** Portable gel extinguisher – the extinguisher is operated with an internal cartridge

Type: **Magnum Water Glue**

**Characteristic:**

- The interruption of the extinguishing and also the intermittent usage is possible all the time.
- Valve made of a high quality, glass fiber reinforced plastic, with black coated aluminium cap nut
- High quality EPDM hose, with a lance, attached at the manufacturing.
- Through the polyester coating of the cylinder, outstanding and long-lasting corrosion protection.
- The polymer inner coating provides excellent and also long-term protection against any type of rust.
- Suitable for electrical objects up to 1000 V, with a minimum distance of 1 m.
- High quality wall bracket for the easy installation.



Compliant with the European Standard DIN/EN3  
TÜV-certified pressure cylinder  
CE-marked  
Management System certified according to ISO 9001

**Technical details:**

Amount of the agent	6 l	9 l
Testing object	13 A	21 A
Range of operating temperature	from 5°C to +60°C	from 5°C to +60°C
Test pressure	27 bar	27 bar
Bursting pressure	min. 55 bar	min. 55 bar
Material of the valve	PA 6 GF 30	PA 6 GF 30
Material of the cylinder	DC 04	DC 04
Propellant	CO <sub>2</sub>	CO <sub>2</sub>
Amount of propellant	50 gr.	70 gr.
Type of agent	GlueX	GlueX
Inner coating	Polymer	Polymer
Coating	Polyester	Polyester
Gross weight (approx.)	11,5 kg	16,7 kg
Dimension ( LxWxH) cm	28x16,5x57,5	30x19x57,5
Packaging	cardboard	cardboard
Function time	approx. 26 sec.	approx. 35 sec.
Range of throw approx.	approx. 6 m	approx. 6 m