



Fire Fighting Solutions

When It Comes To Your Safety Only The BEST Is Good Enough

**BAVARIA**

## **BAVARIA®** Wheeled Water Mist Fire Extinguishers External Pressure Cylinder Operated

Type

### Maximus 50 AQUA-fog

#### APPLICATIONS

BAVARIA Maximus 50 AQUA-Fog is not only capable of effectively extinguishing the fire, but has a great cooling effect and can excellently insulate the heat radiation. The water fog is displacing the oxygen from the environment of the fire. This cooling effect can also be used to protect the people and the belongings from the heat.



**BAVARIA** EGYPT (S.A.E.)  
Gisir El Suez St. Block 109, Industrial Zone  
Ismailia Desert Road, Cairo - Egypt  
P O Box: 2016/11111 Cairo - Egypt

Tel. : + 20 (2) 2182 0604 / 5 / 6  
Fax : + 20 (2) 2182 0609  
Website : [www.bavaria-firefighting.com](http://www.bavaria-firefighting.com)  
Email : [international.sales@bavaria.com.eg](mailto:international.sales@bavaria.com.eg)



**BAVARIA** Brandschutz Industrie GmbH & Co. KG  
Regensburger StraBe16,  
D-93449 Waldmunchen  
Germany

Tel. : + 49 (0) 997 29 401-0  
Fax : + 49 (0) 997 29 401-17  
Website : [www.bavaria-firefighting.de](http://www.bavaria-firefighting.de)  
Email : [info@bavaria-firefighting.de](mailto:info@bavaria-firefighting.de)

**Germany - Egypt - Lebanon - Sudan**

2 plants in Europe and Middle East, 250 dealers worldwide

## BAVARIA® Wheeled Water Mist Fire Extinguishers

Type: **Maximus 50 AQUA-fog** - External Pressure Cylinder Operated

### Features:

- The interruption of the extinguishing and also the intermittent usage is possible of all time.
- Equipped with a 3 l – nitrogen cylinder.
- The extinguisher is equipped with a 10 m long high pressure hose.
- Through to the polystyrene coating of the cylinder and also the inner coating with the polymer, the extinguisher has a great protection against corrosion.
- Brass valve, with aluminum cap nut, coated black, with an additional safety valve.
- The stable trolley is equipped with rubber wheels.
- Suitable for electrical objects up to 1000 V, with a minimum distance of 1 m.



Manufactured according to European Standard DIN/EN 1866  
TÜV-certified pressure cylinder  
CE marked  
Management System certified according to ISO 9001

### Technical Specifications:

Amount of the agent	50 l
Test object	A
Range of operating temperature	from 0°C to +60°C
Test pressure	31,5 bar
Bursting pressure	min. 55 bar
Material of valve	Nickel plated brass
Material of cylinder	Steel
Propellant	N2
Amount of propellant	160 bar / 3 l
Extinguishing agent	Water
Coating	Polyester
Gross weight (ca.)	83,0 kg
Dimension (LxWxH) cm	48,5x46,5x118
Packaging	Pallet
Functional time	approx. 100 sec.
Range of throw approx.	approx. 9 m

### Warranty:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

\* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.