



## **BAVARIA<sup>®</sup>** Portable Dry Chemical Powder Fire Extinguishers

For Coal Dust Fires - Internal Cartridge Operated

# Quick 12 KO

## APPLICATIONS

**BAVARIA Quick 12 KO is** suitable for dust fires It is used in almost all areas, where there is a risk of dust explosion and where there is an absolute priority to prevent the dust to whirl up during the extinguishing process. The extinguisher has a special nozzle or lance, with which the extinguishing agent (ABC powder) can be brought smoothly, without any high pressure onto the burning object. In order to keep the biggest possible distance from the fire, the longest hoses and nozzles are used.







BAVARIA EGYPT (S.A.E.) Gisr El Suez St. Block 109, Industrial Zone Ismailia Desert Road, Cairo - Egypt P O Box: 2016/11111 Cairo - Egypt



**BAVARIA** Brandschutz Industrie GmbH & Co. KG Regensburger Str. 16 D-93449 Waldmünchen Deutschland

Tel.	: + 20 (2) 2182 0604 / 5 / 6
Fax	: + 20 (2) 2182 0609
Website	: www.bavaria-firefighting.com
Email	: international.sales@bavaria.com.eg
	e e

Tel.	: + 49 (0) 9972 9401 0
Fax	: + 49 (0) 9972 9401 17
Website	: www.bavaria-firefighting.de
Email	: info@bavaria-firefighting.de

Germany - Egypt - Lebanon - Sudan 2 plants in Europe and Middle East, 250 dealers worldwide





## **BAVARIA®** Portable Dry Chemical Powder Fire Extinguishers

### Type: Quick 12 KO - For Coal Dust Fires - Internal Cartridge Operated

#### Features:

- High extinguishing rating.
- Allows intermittent and repeated operation
- Designed with a special brass head
- Special lance mounted onto the extinguisher for a smooth application with low pressure.
- Throughout the special polyester coating of the cylinder, the extinguisher has a high corrosion protection.
- Filled with a special BAVARIA ABC extinguishing powder
- Suitable for electrical systems up to 1000 V, with a min. distance of 1 m.
- Supplied with a high quality wall bracket



Compliant with the European Standard DIN/EN3 TÜV-certified pressure cylinder CE marked Management System certified according oh ISO 9001

#### **Technical Specifications:**

Amount of the agent	12 kg
Range of operating temperature	from -20°C to +60°C
Testing pressure	30 bar
Bursting pressure	min. 55 bar
Material of the valve	Missing / Brass
Material of the cylinder	DC 04
Propellant	CO2
Amount of the propellant	270 gr.
Extinguishing agent	ABC powder
Coating	Polyester
Approx. gross weight	20,0 kg
Approx. unit dimension (LxWxH)	27x19,5x95 cm
Packaging material	Cardboard
Functional time	approx. 20 sec.

#### Warranty:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity
	-

\* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.