BAVARIA



BAVARIA[®] Car Dry Chemical Powder Fire Extinguisher Stored Pressure Operated

CHAMPION







APPLICATIONS

BAVARIA CHAMPION is a versatile fire extinguisher designed for optimum protection against fire hazards of vehicles, households, workshops, and others

EFFICIENCY

High extinguishing performance rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder", and easy to use

RELIABILITY

Robust, functional and permanent reliable technology, safe in vehicle due to its holding bracket & strap

UNIVERSALITY

Suitable for solid and glowing incendiary substances, liquid substances or substances becoming liquid and gaseous substances

CREDENTIALS

Unified operating concept for all types of stored presssure operated extinguishers. Approved EN3, TÜV, CE and ES 8442

SPEED

Pull out safety pin for immediate readiness and press down operating lever for fire fighting

EASY TO HANDLE

Full hand grip handle for best control and safety for one hand operation

ECONOMY

Low maintenance due to identical components throughout the series

OPERATION & IMPLEMENTATION

- Simple and easy-to-use release mechanism
- Perfect amount of extinguishing agent due to ergonomically designed head valve & nozzle

QUALITY

Tel

Fax

DNV

BAVARIA is certified according to Quality, Environment and Management Systems ISO 9001, ISO 14001 and ISO 45001



BAVARIA EGYPT (S.A.E.) Gisr El Suez St. Block 109, Industrial Zone, Ismailia Desert Road, Cairo-Egypt P O Box: 2016/11111 Cairo-Egypt



BAVARIA Brandschutz Industrie GmbH & Co. KG Regensburger StraBe16,

D-93449 Waldmunchen Germany

| Email | : international.sales@bavaria.com.eg |
|---------|--------------------------------------|
| Tel. | : +49 (0) 9972 9401-0 |
| Fax | : +49 (0) 9972 9401-17 |
| Website | : www.bavaria-firefighting.de |
| Email | : info@bavaria-firefighting.de |

: +20 (0) 2 2182 0604 / 5 / 6

: +20 (0) 2 2182 0609

Website : www.bavaria-firefighting.com



BAVARIA[®] Car Dry Chemical Powder Fire Extinguisher - Stored Pressure Operated

FEATURES:

- High extinguishing rating
- Optimum for use in vehicles, households and workshop
- Full hand grip handle for best control and safety for one hand operation
- Allows intermittent and repeated operation
- Safe in vehicle due to its full engineering polymer valve, holding bracket and strap
- Equipped with a pressure gauge for instant pressure indication
- Equipped with pressure check valve
- High quality surface treatment and red polyester coating
- Affords the highest extinguishing rating due to its multipurpose dry chemical powder "BAVARIA Superlative Powder"
- Suitable for electrical equipment up to 1000 V, at minimum distance 1 m



BAVARI

TYPE: CHAMPION MEDIUM HAZARD ★★★★★

European Standard DIN/EN3 Certified

The extinguishing media (dry chemical powder) is certified according to the European Norm EN 615

Egyptian Standard ES 8442 Certified

TÜV (SÜD Deutschland) Approved Pressure Vessel

Awarded the European (CE) mark

Certified According to International Quality Management System ISO/TS 16949 in the Scope of Vehicles Extinguishers BAVARIA is certified according to Quality, Environment and Management Systems ISO 9001, ISO 14001 and ISO 45001 Bavaria Laboratory Accredited According to the ISO/IEC 17025

TECHNICAL SPECIFICATIONS:

| Capacity | 1 kg | 2 kg | |
|---|--|-----------------------|--|
| Extinguishing Rating | 8A 34B C | 13A 89B C | |
| Operating Temperature Range* | -30 °C to +60 °C | -30 °C to +60 °C | |
| Testing Pressure | 35 bar | 35 bar | |
| Bursting Pressure | Over 70 bar | Over 70 bar | |
| Valve Material | Special engineered polymer | | |
| Shell Material | DC 04 Steel according to DIN EN 10130 | | |
| Extinguishing Agent | MAP-based "BAVARIA Superlative Powder" | | |
| Paint Finish | Surface treatment and 100% polyester coating | | |
| Approx. Gross Weight | 2.4 kg | 4.0 kg | |
| Approx. Unit Dimension (lxwxh) | 15.0 x 10.5 x 29.5 cm | 16.0 x 11.5 x 37.0 cm | |
| * This product is certified to fully operate at temperatures up to +70 °C according to ES 8442 Standard | | | |

| WARRANTY: | |
|-----------------------------|--|
| Period of Warranty | 2 Years |
| Coverage of the Warranty | Against material failure and production defects |
| Method of Warranty Coverage | Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty |
| Warranty Exclusions | Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity |
| | |

* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.